



GH PLANT

GH64, GH94 & GH1054

GH64

This is the smallest of the GH plant trailer range. With a bed size of 6' x 4' wide and a payload of 1230kg (gross weight 1500kg), the GH64 is designed for smaller items of plant such as micro-excavators.

Compact yet robust, this is a neat and convenient single axle trailer that can be towed behind a car.

As with all GH models, its galvanized welded construction and leaf spring suspension ensures it will withstand tough conditions.

GH64 model is available with two ramp options, a 3'9" ramp with mesh infill or a longer 4'9" bevelled ramp with no infill.

GH94

The GH94 is an extremely versatile plant trailer. A 24mm thick platform makes the GH94 particularly suitable for transporting a wide selection of plant, including tracked excavators, and many items of wheeled equipment such as rollers.



GH64 with 4'9" bevelled ramp



GH94 with 195/55R10C tyres and 3'9" ramp with mesh infill





GH94BT with 165R13C tyres and 4'9" bevelled ramp



GH1054 with 4'9" bevelled ramp

Two self supporting knife edge ramp options are available on all GH models. The 3'9" mesh infill ramp (see opposite) provides the benefits of a full width ramp. The 4'9" bevelled ramp offers significant benefits when loading plant - As well as a 13° loading angle, the ramp is bevelled to help guide the tracks or wheels of the plant being loaded, which provides reassurance to the operator.

GH94

cont. . .

The 9' length of the GH94 provides ample loading space behind the rear axle. This enables a full range of mini-excavators to be loaded along with machines with a more central centre of gravity, such as hi-tip dumpers.

The GH94 is available with 195/55R10C tyres, or larger 165R13C tyres. Trailers with larger tyres are constructed to a beavertail specification to maintain the excellent loading angle of 13°. Beavertail models are also 3" wider than flatbed models.

GH94 models on both 10' and 13' tyres are offered with either the 3'9" ramp with mesh infill or the 4'9" bevelled ramp with no infill.

Both GH94 models are available with a patented breaker storage option. Further details can be found overleaf.

GH1054

The GH1054 offers one of the highest payloads ever produced by Ifor Williams Trailers. With its robust, welded construction and heavily treaded 185/70R13C tyres, the GH1054 is a rugged trailer for demanding conditions.

To provide the highest possible payload, the GH1054 floor construction is suitable only for tracked excavators.

FEATURES & OPTIONS

Standard features on all models include, walk-on steel treadplate mudguards, spring assisted ramp with integrated ramp supports, bucket rest, heavy duty jockey wheel and five pairs of 500kg lashing points per trailer.

Coupling eye options are also available as an alternative to the standard coupling fitted to the trailer.



BREAKER BOX

Available on GH94 models, the breaker storage is designed to suit an Atlas Copco SB102 hydraulic breaker. This enables secure storage and transportation of the breaker whether attached to or detached from the excavator boom. Breaker Storage combines as a bucket rest when breaker is not attached.



STANDARD BUCKET REST

Raised bucket rest with lip for excavator teeth.



WINCH & BRACKET

1050kg Manual Winch with Bracket. Attached to the bucket rest, the winch provides loading assistance to lighter items of plant that cannot be driven onto the trailer.



SPECIFICATION & PRICE LIST

	Tyres	Gross Weight	Payload	Interior Width	Interior Length	Delivery Charge to Mainland Distributor	3'9" Ramp with Mesh Infill	4'9" Bevelled Ramp	Heavy Duty Jockey Wheel	Spring Assisted & Self Supporting Ramp	Five Pairs of Lashing Points	Bucket Rest	Beavertail	Spare Wheel & Bracket	Aluminium Treadplate Floor Covering	1050kg Manual Winch Kit	Breaker Box**
GH64	195/55R10C	1500kg	1230kg*	1230mm / 4'	1880mm / 6'1"	£65	£1,325	£1,325	STD	STD	STD	STD	N/A	STD	£95	£240	N/A
GH94	195/55R10C	2700kg	2220kg	1230mm / 4'	2795mm / 9'1"	£65	£1,630	£1,630	STD	STD	STD	STD	N/A	£95	£160	£240	£400
GH94BT	165R13C	2700kg	2170kg	1310mm / 4'3"	2795mm / 9'1"	£65	£1,565	£1,565	STD	STD	STD	STD	STD	£65	£180	£240	£400
GH1054	185/70R13C	3500kg	2865kg	1626mm / 5'4"	3045mm / 9'11"	£65	£2,165	£2,165	STD	STD	STD	STD	STD	£115	£230	£240	N/A

* Payload includes weight of spare wheel. ** Designed for Atlas Copco SB102 Hydraulic Breaker.

Prices are ex-works and are subject to delivery charges and the VAT rate applicable at the date of supply.

Optional accessories have been priced as factory fit items, ordered with your trailer. If ordered at a later date, your distributor may need to fit the items, which could result in fitting charges being incurred.



IFOR WILLIAMS TRAILERS LTD
Cynwyd, Corwen, Denbighshire LL21 0LB
Telephone +44 (0)1490 412527

sales@iwt.co.uk

www.iwt.co.uk

Product design, descriptions, colours, specifications are correct at the time of going to press. We constantly strive to improve our products and from time to time this may result in changes to our range or to individual models. Please check that design, description, colours and specifications described in this brochure are still valid at the time of placing an order.

Our distributors have extensive product knowledge and will be pleased to offer assistance in the selection of your trailer.

© Ifor Williams Trailers Ltd 2009. All rights reserved. Distributed throughout the UK & Europe.

No part of this publication may be reproduced in any form or by any means, without the written permission of Ifor Williams Trailers Ltd.

Thank you to Major Owen, Penrhyndeudraeth for providing machinery and assistance.